



PROJECT NAME _____

CATALOG NUMBER _____

NOTES _____

FIXTURE TYPE _____

STFR Series

Troffer

Highlights

- Elegant Design
- Power Selector to Change Power
- CCT Tunable (3000K, 4000K, 5000K)
- 50,000 Hours
- Up to 100 Lumens per Watt
- 5 Year Warranty
- 0-10V Dimmable
- 80+ CRI
- UL, DLC Approved



Applications

- Schools
- Offices
- Hospitals

Ordering Guide

Example

LGL-STFR-22-2P-SV

LGL STFR					
LUMINOS GLOBAL	PRODUCT	SIZE	POWER	VOLTAGE	ADDITIONAL OPTIONS
LGL	STFR	22=2X2	2P=30W, 35W, 40W (2x2 Only)	SV=100-277V	EM=Emergency Back Up
		24=2X4	4P=30W, 40W, 50W (2x4 Only)		MS=Motion Sensor



PROJECT NAME _____

CATALOG NUMBER _____

NOTES _____

FIXTURE TYPE _____


STFR Series

Troffer


Technical Overview

Performance Summary	Input Voltage	100-277V	
	Input Frequency	50Hz-60Hz	
	Lumen Efficacy	Up to 100 lm/w	
	Light Output (Photopic)	2P	30W- 3,000 lumens
			35W- 3,500 lumens
			40W- 4,000 lumens
		4P	30W- 3,000 lumens
			40W- 4,000 lumens
			50W- 5,000 lumens
	Working Environment	Indoor	
	Beam Angle	120°	
	Kelvin Switch Options	3000K, 4000K, 5000K	
	CRI	80+	
	Power Factor	>0.95	
	IP Rating	IP44	
Life Span	50,000 hrs		
Dimming Options	0-10V		
Mounting Options	Recessed		

Dimensions



Model LGL-STFR-24



Model LGL-STFR-22

