



PROJECT NAME _____

CATALOG NUMBER _____

NOTES _____

FIXTURE TYPE _____

PST Series

Post Top Light

Highlights

- Architectural Design
- Asymmetrical Distribution
- 50,000 Hours
- 120 Lumens per Watt
- 5 Year Warranty



Applications

- Parks
- Pathways
- General Areas

Ordering Guide

Example

LGL-PST-60-SV-30-B-7-III

| LGL | PST | | | | | | | |
|----------------|---------|----------------|-------------------|----------------|---------------|-------------|--------------------|-------------------------|
| LUMINOS GLOBAL | PRODUCT | POWER | VOLTAGE | CCT | FINISH | CRI | DISTRIBUTION | ADDITIONAL CONTROLS |
| LGL | PST | 40= (40W) | SV= (100-277V) | 30= (3000K) | B= (Black) | 7= (70+) | III= (Type III) | Blank= (No Controls) |
| | | 60= (60W) | | 40= (4000K) | | 8= (80+) | IV= (Type IV) | PC= (Photocell) |
| | | 75= (75W) | | 50= (5000K) | | | V= (Type V) | MS= (Motion Sensor) |
| | | 100= (100W) | | 57= (5700K) | | | | |



PROJECT NAME _____

CATALOG NUMBER _____

NOTES _____

FIXTURE TYPE _____

PST Series

Post Top Light

Technical Overview

| | | |
|---------------------|---------------------------|----------------------------|
| Performance Summary | Input Voltage | 100-277V, 347-480V |
| | Input Frequency | 50Hz-60Hz |
| | Lumen Efficacy | Up to 120 lm/w |
| | Light Output | 40W- 5,200 lumens |
| | | 60W- 7,800 lumens |
| | | 75W- 9,750 lumens |
| | | 100W- 13,000 lumens |
| | Working Environment | Outdoor |
| | Beam Angle | Type III, Type IV, Type V |
| | Color Temperature | 3000K, 4000K, 5000K, 5700K |
| | CRI | 70+, 80+ |
| | Power Factor | >0.9 |
| | IP Rating | IP66 |
| | Life Span | >50,000 hrs |
| Dimming Options | 0-10V, PMW, Timer Dimming | |
| Mounting Options | Pole Mount | |

Dimensions

