



PROJECT NAME _____

CATALOG NUMBER _____

NOTES _____

FIXTURE TYPE _____

SPNL Series

Panel Fixture

Highlights

- 50,000 Hours
- Up to 100 Lumens per Watt
- 5 Year Warranty
- 0-10V Dimmable
- Elegant Surface Mounting
(No Bulky Frame Needed)
- UL Approved



Applications

- Restaurants
- Hospitals
- Rooms
- Offices

Ordering Guide

Example

LGL-SPNL-22-40-SV-35

LGL	SPNL				
LUMINOS GLOBAL	PRODUCT	SIZE	POWER	VOLTAGE	CCT
LGL	SPNL	22=2X2	27=27W	SV=100-277V	35=3500K
		24=2X4	40=40W		40=4000K
		14=1X4	50=50W		50=5000K



PROJECT NAME _____

CATALOG NUMBER _____

NOTES _____

FIXTURE TYPE _____

SPNL Series

Panel Fixture

Technical Overview

Performance Summary	Input Voltage	100-277V	
	Input Frequency	50Hz-60Hz	
	Lumen Efficacy	100 lm/w	
	Light Output (Photopic)	2x2	27W- 2,700 lumens
			40W- 4,000 lumens
		2x4	40W- 4,000 lumens
			50W- 5,000 lumens
		1x4	40W- 4,000 lumens
	Working Environment	Indoor	
	Beam Angle	120°	
	Kelvin Switch Options	3500K, 4000K, 5000K	
	CRI	80+	
	Power Factor	>0.95	
	IP Rating	IP44	
Life Span	50,000 hrs		
Dimming Options	0-10V		
Mounting Options	Surface Mount		

Dimensions

