PROJECT NAME

FIXTURE TYPE

CATALOG NUMBER

ADDITIONAL NOTES

FCW Series

Wallpack

E475876

Applications

- Walls
- Perimeter Lighting
- Facades



Highlights

- 50,000 Hours
- 5 Year Warranty
- Weather Resistant
- 125 Lumens per Watt
- Self Contained EM Back Up
- Marine Turtle Safe Option Available

Ordering Guide

Example **LGL-FCW-15-SV-30-N-T3-B-PC**

LGL	FCW							
LUMINOS GLOBAL	**PRODUCT**	**POWER**	**VOLTAGE**	**CCT**	**DIMMING**	**DISTRIBUTION**	**FINISH**	**ACCESSORIES**
LGL	FCW	15= 15W	SV= 100=277V	30= 3000K	D= Dimmable	T3= Type III	B= Black	PC= Photocell
		25= 25W	HV= 340-480V	40= 4000K	N= Non Dimmable		DB= Dark Bronze	EM= Emergency Backup
		30= 30W		50= 5000K			S= Silver	MS= Motion Sensor
		40= 40W		57= 5700K				
		70= 70W		MTS= Marine Turtle Safe				

© 2026 Luminos Global, Inc. | www.luminosglobal.com

PROJECT NAME

FIXTURE TYPE

CATALOG NUMBER

ADDITIONAL NOTES

FCW Series


Wallpack

E475876


Technical Overview

Performance Summary	
Input Voltage	100-277V
Input Frequency	50Hz-60Hz
Lumen Efficacy	125 lm/w
Light Output (Photopic)	15W- 1,875 lumens
	25W- 3,125 lumens
	30W- 3,750 lumens
	40W- 5,000 lumens
	70W- 8,750 lumens
Working Environment	Outdoor
Beam Angle	Type III
Kelvin Switch Options	3000K, 4000K, 5000K, 5700K, Marine Turtle Safe
CRI	70+
Weight	3.57lbs (15W, 25W & 30W), 6.53lbs (40W & 70W)
Power Factor	>0.95
IP Rating	IP65
Life Span	50,000 hrs
Dimming Options	0-10V
Mounting Options	Surface Mount

Dimensions



Model No
LGL-FCW-15
LGL-FCW-25
LGL-FCW-30



Model No
LGL-FCW-40
LGL-FCW-70

PROJECT NAME

FIXTURE TYPE

CATALOG NUMBER

ADDITIONAL NOTES

FCW Series

Wallpack


E475876

Accessories & Mounting




Photocell

120-277Vac input, IP65 rating




Wall mounting

Photometry



Type III
30W



Type III
40W, 70W

Bug Ratings

PART NUMBER	BUG RATING
LGL-FCW-15	B1 U0 G1
LGL-FCW-25	B1 U0 G1
LGL-FCW-30	B2 U0 G1
LGL-FCW-40	B1 U0 G1
LGL-FCW-70	B3 U0 G3